

Type	Sg hardheid		Blok lengte mm	Netto Blok- hoogte	Dichtheid kg/m³	Hardheid 40% N	Drukweer stand 40% kPa	Kleur
------	----------------	--	----------------------	--------------------------	--------------------	-------------------	------------------------------	-------

POLYETHER (T) :

18H	18100		2460		17	100	2,4	Wit
23Z	23090		2500		23	90	2,1	Wit
25Z	25090		2500		25	90	2,0	Wit
25H	25170		2500		25	170	4,0	Grijs
30Z	33120		2500		33	120	3,0	Bl.Marmer
30H	30180		2500	1150	30	180	4,3	Wit
35M	35180		2500	1190	35	180	4,5	Blauw
35H	35220		2500	1150	35	200	5,4	Wit
38HH	40300		2500	1100	40	320	8,0	L.Groen
50SH	50320		2460		50	320	8,0	L.Geel
65SH	65470		2500	630	65	470	11,0	Grijs

KOUD SCHUIM (HR) :

KS30Z	30090		2460		30	90	2,2	Beige
KS35Z	35060		2500		35	60	1,8	Bl.Marmer
KS38M	38145		2500		38	165	4,0	Donker Zalm
KS40Z	40120		2500		40	120	3,0	Roze
KS40H	40190		2460		40	200	4,9	Grijs
KS44H	44160		2460		44	165	4,2	Wit
HR 45055	45220		2400		45	220	5,5	Orchidee
KS50Z	50120		2500	860	50	120	3,0	L. Geel
KS50H	50160		2460		50	165	4,2	Geel

CMHR-SCHUIM :



CMHR27Z	27080		2460		27	80	2,0	Beige
CMHR35M	35150		2460		35	150	3,6	Grijs
CMHR40H	43160		2460		43	160	4,0	Oker
CMHR50H	50180		2460		50	180	4,5	Wit
CMHR60EH	60240		2460		60	240	5,9	Wit
CMHR65SH	65340		2460		65	340	8,0	Wit

PANTERA-SCHUIM:



PAN 50	40065		1820		40	65	1,6	Creme
NAUTIC100	50110		2460		50	110	2,8	Bl.Marmer
NAUTIC130	50140		2460		50	140	3,7	Bl.Marmer
NAUTIC150	50170		2460		50	170	4,3	Bl.Marmer
NAUTIC170	50230		2460		50	230	5,7	Bl.Marmer

DRYFEEL :



DRYFEEL	XS		1400	500	23	60	1,5	L. Geel
DRYFEEL	MS		1400	500	24	110	2,8	L. Geel
DRYFEEL	S		1400	500	33	180	4,5	L. Geel
DRYFEEL	F		1500	500	30	300	7,5	L. Geel

SPECIALTIES:

VISCO	30		1420/1620/1820	95	30	60	1,5	L.Blauw
VISCO	52		1820	85	52	80	2,5	L.Geel
PRESS 140	140		1600		140			Bont
NA40016	40		2500	850	40	65	1,6	Bl.Marmer
HR 25015	25		1500	105	25		1,5	L/Blauw
NA40031	40125		2400	105	38	125	3,1	Bl.Marmer